

# NOVA

Dependable Gas Analysis Solutions

## 7900 SERIES SINGLE & MULTI-GAS INDUSTRIAL PROCESS GAS ANALYZERS



### APPLICATIONS

For continuous monitoring of any combination of gases such as oxygen (O<sub>2</sub>), methane (CH<sub>4</sub>), carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), and hydrogen (H<sub>2</sub>) for industrial processes including heat treating atmospheres.

### FEATURES

- Sensitive infra-red detectors for CO, CO<sub>2</sub>, and CH<sub>4</sub>
- Thermal conductivity detector for H<sub>2</sub>
- Long life (4-5 years) electrochemical oxygen sensor; both PPM and % ranges available
- Sensors/detectors temperature-controlled or compensated for maximum stability
- Bright digital display for each gas
- Built-in sample pump or pressure regulator
- Easy to maintain modular layout

### OPTIONS

- Dielectric ceramic sensor for standard or low range dew point
- Hi/Low gas, low flow, and diagnostic alarms available
- Isolated analog, RS232, RS485, MODBUS®, and Ethernet outputs available
- Sample conditioning systems available for removal of moisture, acidic gas, and dust
- Cabinet purge system available for use in hazardous areas
- Automatic calibration with touch screen LCD display
- Cabinet coolers / heaters can be fitted to most models
- Heated filters and high temperature probes



7903D 3 Gas with Automatic Calibration in NEMA 4 Enclosure

### CALIBRATION

- Ambient air for O<sub>2</sub> span and to zero all other gases
- Analyzed calibration gas with representative concentrations for span off all other gases

NOVA ANALYTICAL SYSTEMS

[www.nova-gas.com](http://www.nova-gas.com)

## DESCRIPTION

The Nova 7900 Series Heat Treat Analyzer System utilizes high stability infrared detectors for the simultaneous measurement of CO, CO<sub>2</sub>, and CH<sub>4</sub>. In addition, the analyzer can also be supplied with a non-consumable, long life thermal conductivity cell for H<sub>2</sub> that is compensated for the interference effects of CO, CO<sub>2</sub>, and CH<sub>4</sub>. This ensures that H<sub>2</sub> will always read correctly regardless of the background gas composition. A long-life electrochemical sensor is used for PPM or % O<sub>2</sub> analysis. Sensors are temperature-controlled or temperature-compensated for maximum stability. All detected gases have a separate digital readout and linear recorder output. Various versions available for either exothermic or endothermic atmosphere gases, or for other industrial process gases. Calculations can be displayed such as gas ratios and heating value of flammable gases.

## ENCLOSURES

Three types of enclosures are available. All tubing connections are 1/4" SS FPT.

- 7900N4 - Wall mounted NEMA4 (IP65) enclosure rating
- 7900N4X - Wall mounted corrosion-resistant NEMA4X (IP65) enclosure rating
- 7900RM - 19" (483mm) rack mounted, on sliding rails

## SPECIFICATIONS

*Nova reserves the right to specification changes which may occur with advances in design without prior notice.*

### Description

**Method of Detection:** NDIR infrared detector for CO, CO<sub>2</sub>, & CH<sub>4</sub>; thermal conductivity cell for H<sub>2</sub>; Long life electrochemical sensor for O<sub>2</sub>

**Ranges Available:** 0 - 2,000 PPM to 0 - 25.0% O<sub>2</sub>      0 - 1.00%, 0 - 50.0% CH<sub>4</sub>  
*(Other gas ranges may also be available)*      0 - 1.00%, 0 - 30.0% CO      0 - 2.0%, 0 - 50.0% H<sub>2</sub>  
0 - 1.00%, 0 - 50.0% CO<sub>2</sub>

**Resolution:** 0.1%, 1 PPM

**Accuracy and Repeatability:** ± 1% of full scale on all gases

**Drift:** Less than 2% of full-scale per month

**Response Time (T-90):** 20-30 seconds to 90% step change

**Ambient Temperature Range:** 32-122°F (0-50°C). Lower temperatures -5°F (-20°C) with Cold Weather Package.

**Linearity:** ± 1% of full scale

**Size and Weight:** Physical data will vary depending on model and enclosure required

**Power:** 115VAC 60Hz (220VAC 50Hz available)

**Output Options:** 4-20mA into 500 ohms non-isolated standard  
Isolated 4-20mA, RS232, RS485, MODBUS®, Ethernet outputs optional

**Alarms:** High and/or low alarm contacts available, relay contacts SPDT 5A @ 220VAC rating.  
Low flow alarm optional

*Modbus® is a Registered Trademark of the Modbus Organization, Inc.*



NOVA ANALYTICAL SYSTEMS  
A UNIT OF TENOVA GOODFELLOW INC.

IN USA:  
1925 Pine Avenue • Niagara Falls, NY • 14301  
Tel: 1-800-295-3771 • 716.285.0418 • Fax: 716.282.2937  
IN CANADA:  
270 Sherman Avenue North • Hamilton, ON • L8L 6N5  
Tel: 905.545.2003 • Fax: 905.545.4248  
email: sales@nova-gas.com  
websales@nova-gas.com



www.nova-gas.com